# **SINGLE CHANNEL**

# **Advanced Battery Management System**

#### CAT # NDV9



## **Voltage Options**

12V	NDV9-12V
24V	NDV9-24V
48V	NDV9-48V
51V	NDV9-51V
102V	NDV9-102V

# **Key Benefits**

- ✓ Advanced iONbus® Technology
- **⊘** NeverDie® Power Reserve
- **⊘** Suitable for Various Applications

#### **Reliable Power, Seamless Integration**

Experience peace of mind with Lithionics Bluetooth app for real-time monitoring and diagnostics. Optimize your battery usage utilizing our innovative Battery Management System (BMS) that provides advanced protection ensuring battery safety and longevity. Easily connect multiple batteries to a single BMS by plugging directly into a combiner box.


# **DIMENSIONS**


# Size (L x W x H):

13.0" x 23.7" x 4.0" (330.2mm x 602.0mm x 101.6mm)

## Weight:

8.0lbs (3.6kg)





## **SPECIFICATIONS**

#### **VOLTAGE AND CAPACITY**

12.8V to 102.4V (4S-32S) 400A\* Amperage Continuous

\*325A continuous with a single 4/0 Wire, 400A continuous requires 350MCM or 2x4/0 cables connected to each of the BMS terminals for heat dissipation

# AMPSEAL-14 Functions (Support depends on specific AMPSEAL-14 wire harness):

Alternator Control, Generator Control, Remote Lighted ON/OFF, Alarm Battery Low LED, Emergency- Stop, RS232, Aux. External Power Input **Bluetooth®:** 

Includes App (iOS, Android). Monitoring, Datalogging, Firmware Updates, PIN Security

#### **FEATURES**

#### **Protection Features:**

Reserve Cut-Off, Pack Over and Under Voltage, Cell Over and Under Voltage, Cell Over and Under Temperature, Contactor Over-Temperature, Contactor State, Short Circuit, Over Current, Pre-charge circuit **Optional Features:** 

RS232 (In place of Bluetooth), Ethernet TCP/IP, NMEA 2000 Port

#### **Easily Integrates With:**

NCC CANbus Chargers, IonGauge Display, Victron Cerbo Support, Wakespeed WS500 Alternator Regulator, RV-C CANbus Compliant Devices, NMEA 2000 Compliant Devices, SmartPower Alternator Series, Lithionics 3,000W Inverter-Charger



DS-018

#### **MECHANICAL**

**Terminal Size: 5/16-18** 

**Terminal Torque:** 108-132in-lbs (12.2-14.9Nm)

**Ingress Protection: IP66** 

**iONbus (M12 Connector):** Combines OptoLoop and RV-C CANbus technology

into one connector
Included Components:

IonBus T-Adapter, 2 IonBus Terminators,

**Terminal Covers** 



## Powering Innovation.

Discover the right lithium replacement system for you. Reach out to Lithionics' expert support team to find your perfect power solution.